

AMENDMENTS TO THE SPECIFICATION

Please replace paragraph [0029] with the following amended paragraph:

[0029] As shown in Figs. 6 and 7, left side crank arm 60B comprises a crank arm body 330, an axle mounting boss 331 having an axle mounting opening 332 with a splined inner peripheral surface 333, and a pedal mounting boss 334 having a pedal mounting opening 335 with a threaded inner peripheral surface 336. In this embodiment, axle mounting boss 331 includes a first mounting ear 337 spaced apart from but in close proximity to a second mounting ear 338. First mounting ear 337 includes an unthreaded (e.g., first) fastener opening 339 and a threaded (e.g., third) fastener opening 340, and second mounting ear 338 includes an unthreaded (e.g., second) fastener opening 341 and a threaded (e.g., fourth) fastener opening 342. A first fastener such as a crank arm bolt 343 having a threaded shank 344 and a head 345 extends through unthreaded fastener opening 339 in first mounting ear 337 and screws into threaded opening 342 in second mounting ear 338 such that head 345 abuts against first mounting ear 337. Similarly, a second fastener such as a crank arm bolt 346 having a threaded shank 347 and a head 348 extends through unthreaded fastener opening 341 in second mounting ear 338 and screws into threaded opening 340 in first mounting ear 337 such that head 348 abuts against second mounting ear 338. Crank arm bolts 343 and 346 thus tighten first mounting ear 337 and second mounting ear 338 towards each other for clamping axle mounting boss 331 around axle 59 as discussed below.